Spray Gun Series

Gg-138

Gravity Feed Detailing Spray Gun

Features:

- Features 3 built-in regulators to control air flow, paint flow and material width.
- Stainless steel needle and fluid tip allow use with water base paints
- Significant reduction of operating cost



Technical Data			
A :	Bar	2.6 – 4.0	
Air pressure	Psi	38 – 60	
Air inlet		1/4"	
Fluid inlet		M14 x 1.0P	
Air concumption	Cfm	3 – 5	
Air consumption	L/min	85 – 142	
Waight	Lbs	0.66	
Weight	Kgs	0.3	
Capacity of nylon cup		125cc	
Standard fluid tip size	mm	0.8	
Optional nozzle size	mm	0.5, 1.0, 1.1, 1.2, 1.5	
All automotive colors, high solids colors & clear coats			
Optional 125CCAC	125cc	Alum cup	
Sound power dBA <70			
Repair kit is available in additional order			

Spray Gun Series

Gg-148

Deluxe Gravity Feed Spray Gun

Features:

- Provide high quality topcoat finishes in automotive, furniture construction etc.
- Compact & lightweight
- Easily maintained



Technical Data			
	Bar	3.5 – 5.0	
Air pressure	Psi	50 – 70	
Air inlet	·	1/4"	
Fluid inlet		M16 x 1.5P	
A :	Cfm	14	
Air consumption	L/min	396	
Waight	Lbs	1.1	
Weight	Kgs	0.5	
Capacity of nylon cup	Liter	0.6	
Standard fluid tip size	mm	1.4	
Optional nozzle size	mm	1.0, 1.2, 1.5, 1.7, 2.0	
All automotive colors, high s	solids colors & clear coats		
Optional 600CCAC	0.6 L	Alum cup	
Optional 1000CCAC	1.0 L	Alum cup	
Sound power dBA <70			
Repair kit is available in additional order			

Spray Gun Series

Gg-146HWB

Water Base HVLP Gravity Feed Detailing Spray Gun

Features:

- High transfer efficiency with low air consumption
- Provides wide fan pattern with superior atomization
- Perfect for waterborne material applications
- Less overspray & more paint coverage
- Good idea for small paint jobs
- Gun weight only 0.66 lbs (0.30 kgs)
- Die cast aluminum gun body, satin chrome body, easy to clean
- Stainless steel nozzle & needle

Technical Data		
A in massauma	Bar	2
Air pressure	Psi	29
Air Cap Pressure		<10 psi
Air inlet		1/4"
Fluid inlet		1/4"
Air concumption	Cfm	4
Air consumption	L/min	112
Waight	Lbs	0.66
Weight	Kgs	0.30
Capacity of alum cup		125cc
Standard fluid tip size	mm	1.0
Optional nozzle size	mm	0.5, 0.8, 1.2, 2.0
All automotive colors, high solids colors & clear coats		
Comes complete with regulator		R11
Optional 125CCCM 125cc		Nylon cup
Sound power dBA < 70		
Repair kit is available in additional order		



Spray Gun Series

Gg-152HWB

Water Base HVLP Gravity Feed Spray Gun

Features:

- High transfer efficiency with low air consumption
- Provides wide fan pattern with superior atomization
- Perfect for waterborne material applications
- Less overspray & more paint coverage
- Good idea for medium to large paint jobs in the auto refinishing industry
- The paint will pass through places by stainless steel
- Gun weight only 1.1lbs (0.5kgs)
- Die cast aluminum gun body, satin chrome body, easy to clean

Technical Data		
۸٠	Bar	2
Air pressure	Psi	29
Air Cap Pressure		<10 psi
Air inlet		1/4"
Fluid inlet		3/8"
Air consumption	Cfm	10
Air consumption	L/min	283
Waight	Lbs	1.17
Weight	Kgs	0.53
Capacity of nylon cup	Liter	0.6
Standard fluid tip size	mm	1.4
Optional nozzle size	mm	1.0, 1.2, 1.3, 1.5, 1.6, 1.8
All automotive colors, high s	olids colors & clear coats	
Comes complete with regular	tor	Optional
Optional 600CCNCM	0.6 L	Alum cup
Optional 1000CCACM	1.0 L	Alum cup
Sound power dBA < 70		
Repair kit is available in add	itional order	·

Spray Gun Series

Gg-334HWB

Water Base HVLP Gravity Feed Spray Gun

Features:

- High transfer efficiency with low air consumption
- Provides wide fan pattern with superior atomization
- Perfect for waterborne material applications
- Less overspray & more paint coverage
- Good idea for medium to large paint jobs in the auto refinishing industry
- The paint will pass through places by stainless steel
- Gun weight only 1.06lbs (0.48kg)
- Die cast aluminum gun body, satin, nickel body, easy to clean

Technical Data		
A in massauma	Bar	3
Air pressure	Psi	43
Air inlet		1/4"
Fluid inlet		M16 x 1.5P
Air consumption	Cfm	10
Air consumption	L/min	283
Waight	Lbs	1.06
Weight	Kgs	0.48
Capacity of nylon cup	Liter	0.6
Standard fluid tip size	mm	1.3
Optional nozzle size	mm	1.0, 1.2, 1.4, 1.6, 1.8, 2.0
All automotive colors, high solic	ls colors & clear coats	
Comes complete with regulator		Optional
Optional 600CCAC	0.6 L	Alum cup
Optional 1000CCAC	1.0 L	Alum cup
Sound power dBA < 70		
Repair kit is available in additional order		

Spray Gun Series


Gg-334RWB

Water Base LVLP Gravity Feed Spray Gun

Features:

- High transfer efficiency with low air consumption
- Provides wide fan pattern with superior atomization
- Perfect for base coat, clear coat, solvents & waterborne material applications
- Less overspray & more paint coverage
- Good idea for medium to large paint jobs in the auto refinishing industry
- The paint will pass through places by stainless steel
- Gun weight only 1.06lbs (0.48kg)
- Die case aluminum gun body, satin nickel plated body easy to clean

Technical Data		
A:	Bar	2
Air pressure	Psi	29
Air inlet		1/4"
Fluid inlet		M16 x 1.5P
Air consumntion	Cfm	10
Air consumption	L/min	283
Waight	Lbs	1.06
Weight	Kgs	0.48
Capacity of nylon cup	Liter	0.6
Standard fluid tip size	mm	1.4
Optional nozzle size	mm	1.0, 1.3, 1.6, 1.8, 2.0, 2.5
All automotive colors, high solid	s colors & clear coats	
Comes complete with regulator		Optional
Optional 600CCAC	0.6 L	Alum cup
Optional 1000CCAC	1.0 L	Alum cup
Sound power dBA <70		
Repair kit is available in additional order		



Spray Gun Series

Gg-834H

HVLP Gravity Feed Spray Gun

Features:

- High transfer efficiency with low air consumption
- Provides wide fan pattern with superior atomization
- Environmental Friendly
- Die cast aluminum gun body, satin chrome body, easy to clean
- Stainless steel fluid nozzle & needle



Technical Data			
Technical Data			
Air pressure	Bar	2	
All pressure	Psi	29	
Air Cap Pressure		<10 psi	
Air inlet		1/4" NPS (PS)	
Fluid inlet		M16 x 1.5P	
A :	Cfm	10	
Air consumption	L/min	283	
W. 1.	Lbs	0.95	
Weight	Kgs	0.43	
Capacity of nylon cup	Liter	0.6	
Standard fluid tip size	mm	1.3	
Optional nozzle size	mm	1.0, 1.2, 1.4, 1.5, 1.6, 1.8, 2.0	
All automotive colors, high	solids colors & clear coats		
Optional 600CCAC	0.6 L	Alum cup	
Optional 1000CCAC	1.0 L	Alum cup	
Sound power dBA <70			
Repair kit is available in additional order			

Spray Gun Series

Gg-834HWB

Water Base HVLP Gravity Feed Spray Gun

Features:

- High transfer efficiency with low air consumption
- Provides wide fan pattern with superior atomization
- Environmental Friendly
- Die cast aluminum gun body, satin chrome body, easy to clean
- Stainless steel fluid nozzle & needle



Technical Data		
A :	Bar	2
Air pressure	Psi	29
Air inlet		1/4" NPS (PS)
Fluid inlet		M16 x 1.5P
Air consumption	Cfm	10
	L/min	283
Waight	Lbs	0.95
Weight	Kgs	0.43
Capacity of nylon cup	Liter	0.6
Standard fluid tip size	mm	1.3
Optional nozzle size	mm	1.0, 1.4, 1.6, 1.8, 2.0
All automotive colors, high solids colors & clear coats		
Sound power dBA < 70		
Repair kit is available in additional order		

Spray Gun Series

Gg-834R

LVLP Gravity Feed Spray Gun

Features:

- High transfer efficiency with low air consumption
- Provides wide fan pattern with superior atomization
- Environmental Friendly
- Die cast aluminum gun body, satin chrome body, easy to clean
- Stainless steel fluid nozzle & needle



Technical Data		
A	Bar	1.5
Air pressure	Psi	21
Air inlet		1/4" NPS (PS)
Fluid inlet		M16 x 1.5P
A	Cfm	7
Air consumption	L/min	196
Wainle	Lbs	0.95
Weight	Kgs	0.43
Capacity of nylon cup	Liter	0.6
Standard fluid tip size	mm	1.4
Optional nozzle size	mm	1.0, 1.3, 1.5, 1.6, 1.8, 2.0, 2.5
All automotive colors, high	solids colors & clear coats	
Optional 600CCAC	0.6 L	Alum cup
Optional 1000CCAC	1.0 L	Alum cup
Sound power dBA <70		
Repair kit is available in additional order		

Spray Gun Series

Gs-144

Suction Feed Spray Gun

Features:

- Features 3 built-in regulators to control air flow, paint flow & material width
- Stainless steel needle & fluid tip allow use with water base paints
- Significant reduction operating coats



Technical Data		
A :	Bar	6
Air pressure	Psi	85
Air inlet		1/4"
Fluid inlet		3/8"
	Cfm	16
Air consumption	L/min	453
Weight	Lbs	2.2
Weight	Kgs	1
Capacity of nylon cup	Liter	1
Standard fluid tip size	mm	1.7
Optional nozzle size	mm	1.0, 1.4, 2.0, 2.3, 2.5
All automotive colors, clears, primers & high viscosity material		
Sound power dBA <70		
Repair kit is available in additional order		

Spray Gun Series

Gs-150

Suction Feed Spray Gun

Features:

- Suitable for all types of refinish primers and paints
- Medium solids, colors, base & clears coats



Technical Data		
	Bar	3 – 6
Air pressure	Psi	43 – 90
Air inlet		1/4"
Fluid inlet		3/8"
A:	Cfm	12 – 15
Air consumption	L/min	337 – 421
W/.'.l.	Lbs	2.3
Weight	Kgs	1.05
Capacity of nylon cup	Liter	1
Standard fluid tip size	mm	1.6
Optional nozzle size	mm	1.5, 1.8, 2.0
With air adjustable valve model #: Gg-150V		
Sound power dBA < 70		
Repair kit is available in additional order		

Shop Tool & Accessories

AI Tool Set

Box set contains:

Description	Quantity
Angle-adjustable toolbox with intergraded	1
light source	
Multi LED detachable Flashlight (batteries	1
included)	
Socket Wrench	1
Socket Adaptor	3
Sockets – 7 mm	1
Sockets – 8 mm	1
Sockets – 9 mm	1
Sockets – 10 mm	1
Sockets – 12 mm	1
Sockets – 13 mm	1
Sockets – 14 mm	1
Sockets – 15 mm	1
Sockets – 17 mm	1
Interchangeable Screwdriver	1
Screwdriver head – Hex	4
Screwdriver head - Philips	3
Screwdriver head - Flat	3
Adjustable Wrench	1
Breaker-grozier pliers	1



Shop Tool & Accessories

DJKA

Dry Air Blow Gun Set

Description:

 Dry air blow gun is used to dry water based paints rapidly by blowing air at the painted or coated surfaces.

- With of adjustable air flow on head
- With 5 x 8 mm x 7.5 m (25 fts.) PU recoil air hose

953K1 Set includes:

- 2 pcs. of adjustable dry air blow gun
- 1 stand
- 2 pcs. of PU recoil air hose
- Assemble accessories
- Optional air blow gun: DJ (non-adjustable dry air blow gun)

Technical Data			
Air pressure	Bar	58 – 65	
	Psi	4 – 4.5	
Max. air pressure	Bar	12	
	Psi	175	
Air inlet		1/4" PS (NPS)	
Air consumption	Cfm	12	
	L/min	350	



Shop Tool & Accessories

DJ

Dry Air Blow Gun



Specification:

Technical data			
Maximum inlet pressure	Bar	7	
	Psi	100	
Working pressure	Bar	3 – 5	
	Psi	43 – 73	
Air consumption	Cfm	12.3	
	L/min	350	
	Psi	60	
Air inlet thread		1/4" PS (NPS)	

MM-69A

18" 4 step masking machine

Features:

- One hand operation
- Lightweight
- Steel frame with double welded for durability
- Easing operation for paper rolls and masking tape



Shop Tool & Accessories

6583SS

Stainless Steel Outlet Paint Gun Washer (Two Gun Capacity Diaphragm Pump)

Interior Dimensions: 14-1/4" x 18-1/2 x 20"

Exterior Dimensions: 16-1/2" x 18-1/2" x 39-3/4"



Atex Approved

Features:

Technical data		
Maximum working air pressure	Psi	100
	Kg/cm ²	8.5
Working air pressure	Psi	40 – 60
	Kg/cm ²	2 – 4
Air consumption	Cfm	2 – 4
Compression ratio of air to liquid		1:1
Maximum liquid flow	Gpm	5
	Lpm	19
	Water tested	3 mins
Air inlet port	Pt	1/4"
Liquid inlet / outlet port	Pt	3/8"
Pump body material		aluminum alloy
Overall size		18-1/2" (w) x 25-1/2" (l) x 40" (h)
Also available diaphragm pump or	nly	

Shop Tool & Accessories

ACU-1

Air Control Unit

- One regulator with 160 lb inverted gauge and air cock
- Additional regulated outlet included
- Filtered main line outlet included
- Air inlet 1/2" F.P.T.
- Filter capacity: 120 cfm
- Regulator capacity: 50 cfm



ACU-3

Air Control Unit

- Two regulator with 160 lb inverted gauge and air cock
- Two regulated outlet included
- Two additional regulated outlets included
- One filtered main line outlet with 200 lb gauge
- Air inlet 1/2" F.P.T.
- Filter capacity: 120 cfm
- Regulator capacity: 50 cfm



Shop Tool & Accessories

1000CCAC

1 litre aluminum gravity cup w/ female thread



1000CCACM

1 litre aluminum gravity cup w/ male thread



600CCAC

0.6 litre aluminum gravity cup w/ female thread



125CCAC

125cc aluminum gravity cup w/ female thread



600CCACM

0.6 litre aluminum gravity cup

w/ male thread



600CCNC

0.6 litre nylon gravity cup w/ female



600CCNCM

0.6 litre gravity cup w/ male thread



125CCNC

125cc nylon gravity cup w/ female thread



Shop Tool & Accessories

GC-12

12 pcs spray gun cleaning kit

- ◆ 1 pc. body cleaning brush with wooden handle
- ♦ 1 pc. external brush with twisted metal wire handle
- ◆ 3 pcs. fluid tube brushes with twisted metal wire handle
- ◆ 1 pc. straight line wire
- ♦ 5 pcs. picks
- ◆ 1 pc. jar of lubricant

GC-17

17 pcs. spray gun cleaning kit

- ◆ 1 pc. extra long 12" pickup tube brush
- ◆ 1 pc. 1/4" HVLP brush
- ♦ 1 pc. 1/2" body cavity brush
- ◆ 1 pc. detail end brush
- ◆ 2 pcs. Nylon bristle parts brush
- ♦ 5 pcs. miniature brush set
- ♦ 6 pcs. precision needle set

GC-22

22 pcs. master spray gun cleaning kit

- 6 pcs. precision needle set
- ◆ 1 pc. handle for precision needle
- ♦ 1 pc. handle for detail end brush
- ◆ 1 pc. paint gun lube, 30cc
- ◆ 3 pcs. detail end brush (1/4", 3/8", 1/2")
- ◆ 1 pc. 12" pickup tube brush
- ◆ 1 pc. nylon bristle parts brush
- ◆ 1 pc. brass power pickup tube brush
- ◆ 1 pc. 1/4" HVLP brush
- ◆ 1 pc. 1/2" body cavity brush







Shop Tool & Accessories

Stainless Steel Strainer for Gravity Paint Guns

Order #: SS1 Single strainer bulk



Order #: G160

Air regulator w/ 160 psi gauge



Order #: Bar

Brass air regulator



Order #: WS

Oil/water separator



Order #: CT166

Bonnet cleaning tool



Order #: VPAD-93

5" Velcro face pad 6 holes spindle 5/16" – 24 unf Thickness: 10mm

